


## Malleable

### Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 2-3/16

Dimension B in Inches: 1 1/16

Dimension C in Inches: 1-9/16

### Application

Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

### Product Information

Material: Malleable Iron

Finish: Zinc electro-plate. Grounding lug: Tin electro-plate

### Certifications & Codes:

Federal Specification Number: A-A-50553

NEMA Standard: FB-1

UL File Number: E20412

UL Standard: UL-514B

UNSPSC: 39121312

**Catalog ID:** 385-14

**UPC Number:** 781747038517

**Description:** Bushing, Insulated, Grounding, Malleable Iron, Size 1 1/2 Inch, 14-4 Lug

**Application:** Used with locknut to terminate service conduit to cabinet. Lug provided for bonding jumper to neutral busbar. Grounding lug: aluminum alloy 6061-T6. Plastic metaliner prevents damage to wire insulation. 1/2" thru 4" rated 150 degree C, 5" and 6" rated 105 degree C.

**Trade Size:** 1 1/2"

**Std Pkg Qty:** 200

**Unit Qty:** 20