



US Steel

Images



[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: .950-1.050
Dimension B in Inches: 1.375
Dimension C in Inches: 2.240
Dimension D in Inches: 1.900
Dimension E in Inches: 1 15/16
Dimension F in Inches: 1 1/4

Application

These watertight fittings, are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Product Information

Material: Steel
Finish: Zinc Electro-Plated

Certifications & Codes:

NEMA Standard: FB-1
UL File Number: E11259, cULus
UL Standard: UL514B
UNSPSC: 39121431

Catalog ID: CG773-1050

UPC Number: 78174727733

Description: Connector, cord grip, straight, steel, k.o. size 1 1/4", cord range, .950-1.050

Application: These watertight fittings, are designed for both indoor and outdoor applications. All fittings can be used in chemical and treatment plants as well as for offshore applications. Straight connector for use with portable cord provides liquid tight and water tight protection. Typical applications include wiring of motors, transformers, advanced machinery, refrigeration, and tools.

Trade Size: 1 1/4

Country of Manufacture: USA

Std Pkg Qty: 25

Unit Qty: 5