

Fire Alarm Cables – Unshielded (continued)

18 AWG – UNSHIELDED

# COND	STR/SOL	DC RESISTANCE (OHMS)	NOM. CAP. (PF/FT)	NOM. O.D. (IN)	AVG. WT. PER MFT (LBS)	PART #
GENERAL PURPOSE – FPL LISTED						
2	SOL	6.5	20	0.134	17	4106
4	SOL	6.5	20	0.170	29	4107 A
6	SOL	6.32	20	0.192	41	4108 c
8	SOL	6.5	20	0.208	52	4109 c
10	SOL	6.5	20	0.244	68	4110 c
RISER RATED – FPLR, CL2R, C(UL), FT4 LISTED						
2	SOL	6.5	19	0.138	17	4306
4	SOL	6.5	19	0.174	34	4307
6	SOL	6.5	19	0.187	44	4308 c
8	SOL	6.5	19	0.208	54	4309 c
10	SOL	6.5	19	0.244	67	4310 c
PLENUM RATED – FPLP, CL2P, C(UL), FT6 LISTED						
2	SOL	6.5	24	0.134	19	4506
4	SOL	6.5	24	0.156	32	4507
6	SOL	6.5	24	0.192	45	4508 c
DIRECT BURIAL – FPL LISTED						
2	STR	6.5	19	0.260	37	4156 c
4	STR	6.5	19	0.295	59	4157 c
6	STR	6.5	19	0.345	76	4158 c
8	STR	6.5	19	0.375	95	4159

A Not twisted
C Reels only