

Fire Alarm Cables – Overall Shielded (continued)

16 AWG – SHIELDED

# COND	STR/SOL	DC RESISTANCE (OHMS)	NOM. CAP. (PF/FT)	NOM. O.D. (IN)	AVG. WT. PER MFT (LBS)	PART #
GENERAL PURPOSE – FPL LISTED						
2	SOL	4.1	46	0.158	29	4206
4	SOL	4.1	46	0.186	49	4207 c
RISER RATED – FPLR, CL2R, C(UL), FT4 LISTED						
2	SOL	4.1	46	0.158	31	4406
4	SOL	4.1	46	0.190	49	4407 c
PLENUM RATED – FPLP, CL2P, C(UL), FT4 LISTED						
2	SOL	4.05	77	0.158	35	4606
4	SOL	4.05	77	0.186	52	4607 c

14 AWG – SHIELDED

# COND	STR/SOL	DC RESISTANCE (OHMS)	NOM. CAP. (PF/FT)	NOM. O.D. (IN)	AVG. WT. PER MFT (LBS)	PART #
GENERAL PURPOSE – FPL LISTED						
2	SOL	2.54	52	0.186	40	4208 c
4	SOL	2.54	52	0.218	67	4209 c
RISER RATED – FPLR, CL2R, C(UL), FT4 LISTED						
2	SOL	2.54	52	0.192	42	4408 c
4	SOL	2.54	52	0.218	72	4409 c
PLENUM RATED – FPLP, CL2P, C(UL), FT6 LISTED						
2	SOL	2.5	86	0.186	44	4608 c
4	SOL	2.5	86	0.218	75	4609 c

12 AWG – SHIELDED

# COND	STR/SOL	DC RESISTANCE (OHMS)	NOM. CAP. (PF/FT)	NOM. O.D. (IN)	AVG. WT. PER MFT (LBS)	PART #
GENERAL PURPOSE – FPL LISTED						
2	SOL	1.6	56	0.218	59	4210 c
RISER RATED – FPLR, CL2R, C(UL), FT4 LISTED						
2	SOL	1.65	56	0.218	60	4410 c
PLENUM RATED – FPLP, CL2P, C(UL), FT6 LISTED						
2	SOL	1.6	96	0.218	63	4610 c

C Reels only