

**Fire Alarm Cables – Unshielded (continued)**

**Construction:**

	Non-Plenum	Plenum	Direct Burial
Conductors	Bare Copper		
Insulation	PP	Low-Smoke PVC	SRPVC
	Conductor Color Code Chart 4		
Jacket	PVC	Low-Smoke PVC	PVC
Colors	Red, White		Black

**Features:**

- Sunlight Resistant (Except Plenum)

**Popular Packaging:**

- Pull Box 500', 1000'
- Reel 500', 1000'
- Consult factory for other packaging options

**16 AWG – UNSHIELDED**

# COND	STR/SOL	DC RESISTANCE (OHMS)	NOM. CAP. (PF/FT)	NOM. O.D. (IN)	AVG. WT. PER MFT (LBS)	PART #
<b>GENERAL PURPOSE – FPL LISTED</b>						
2	SOL	4.15	20	0.154	24	<b>4111</b>
4	SOL	4.15	20	0.180	43	<b>4112 c</b>
<b>RISER RATED – FPLR, CL2R, C(UL), FT4 LISTED</b>						
2	SOL	4.919	20	0.160	24	<b>4311</b>
4	SOL	4.150	20	0.184	43	<b>4312</b>
<b>PLENUM RATED – FPLP, CL2P, C(UL), FT6 LISTED</b>						
2	SOL	4.19	27	0.154	26	<b>4511</b>
4	SOL	4.05	27	0.180	47	<b>4512 c</b>
<b>DIRECT BURIAL – FPL LISTED</b>						
2	STR	3.90	21	0.282	45	<b>4151 c</b>

Unshielded

Conventional

Fire Alarm



C Reels only