




P1546, P2094 THRU P2100

Wt/100 pcs: 58 Lbs (26.3 kg)



Part No.	"A" Degree (rad)	"B" In (mm)	"C" In (mm)
P2094	82½° 1.44	3 9/16 91	1 11/16 43
P2095	75° 1.31	3 9/16 91	1 11/16 43
P2096	67½° 1.18	3 1/2 89	1 3/4 44
P2097	60° 1.05	3 3/8 86	1 7/8 48
P2098	52½° 0.92	3 1/4 83	2 1/16 52
P1546	45° 0.79	3 76	2 5/16 59
P2099	37½° 0.65	3 1/2 89	1 13/16 46
P2100	37½° 0.65	2 11/16 68	2 5/8 67

Standard Dimensions for 1 5/8" (41mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/16" (14mm); Hole Spacing - From End: 13/16" (21mm); Hole Spacing - On Center: 1 7/8" (48mm); Width: 1 5/8" (41mm); Thickness: 1/4" (6mm)

MATERIAL

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

FINISHES

Fittings are available in:

Perma-Green III (GR),

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and

Plain (PL).

Project: _____

Approval Stamp:

Architect / Engineer: _____

Date: _____ **Phone:** _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____