

59416C

AF6 10-12 ANCHOR W/FLANGE 1/4"

UPC: 085937997302

Country of Origin:

UNSPSC: 31162103

**Not Available**

Commodity: Wall anchors



*The specially formulated polypropylene body flows into and locks up with any undercuts in the hole, bonding the screw to the wall and sealing the hole to prevent moisture from entering.*

**Product Attributes**

Brand Name	Minerallac Company
Sub Brand	Cully
Type	Hollow Wall Anchor
Special Features	In solid walls (concrete, masonry, brick, etc.) the ALLIGATOR anchor extrudes up to 2x its original length & bonds the screw to wall.
Size	#10-12 (AF6)
Diameter	0.250" IN
Length	1.188" IN
Minimum Embedment Depth	1.750" IN
Drill Size	1/4" IN
Screw Size	#6 – #12
Head Type	Flanged
Material	Polypropylene
Tension Strength	With #10 SMS in 1/2" Drywall: 69 LB; in 3500 PSI Concrete: 675 LB; With #14 SMS in 4000 PSI Concrete: 2,633 LB
Shear Strength	With #10 SMS in 1/2" Drywall: 153 LB

Item Status: Active  
Standard Qty: 100

Minerallac Company

Tel: 800-927-3293  
Fax: 800-824-8942  
www.minerallac.com