HellermannTyton

109-00026



Article Number: 109-00026

Q Tie, 16.5" Long, 120lb Tensile Strength, PA66, Natural, 100/pkg

RoHS

Base Data

Local Order Number	109-00026	
Туре	Q120R	
Color	Natural (NA)	
Features and Benefits	 Open-head design with easily detectable slot opening allows for swift and easy insertion Pre-lock feature allows for a temporary hold The large ribbed tail permits an ergonomic installation Two rails on the strap ensure guidance through the cable tie head 	
Product Description	Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.	
Fixation Method (FF)	None	
Identification Plate Position	none	
Releasable Closure (Yes/No)	No	
Tie Closure	plastic pawl	
Variant	Inside Serrated	
Short Description	Q Tie, 16.5" Long, 120lb Tensile Strength, PA66, Natural, 100/pkg	

Product Dimensions

Minimum Tensile Strength (imperial)	120.0 lbs
Minimum Tensile Strength (N)	530 N
Length L (imperial)	16.5 "
Length L (metric)	420 mm
Width W (imperial)	0.3 "
Width W (metric)	7.7 mm
Bundle Diameter min (imperial)	0.12 "
Bundle Diameter min (metric)	6.0 mm
Bundle Diameter max (imperial)	4.3 "
Bundle Diameter max (metric)	110.0 mm
Thickness T (imperial)	0.07 "
Thickness T (Metric)	1.8 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes

© HellermannTyton 2014