

151-00432



Article Number: 151-00432

VHB Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, Black, 100/pkg



## Base Data

Local Order Number 151-00432

Type MB3APT

Color Black (BK)

- Features and Benefits**
- Secures with a high temperature, VHB adhesive backing for heavy bonding applications.
  - Can also be secured using two or four screws; providing multiple options.
  - For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** VHB Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, Black, 100/pkg

## Product Dimensions

Length L (imperial) 0.75 "

Length L (metric) 19.0 mm

Width W (imperial) 0.75 "

Width W (metric) 19.0 mm

Cable Tie Width Max (imperial) 0.14 "

Cable Tie Width max. (metric) 4.1 mm

Height H (imperial) 0.18 "

Height H (metric) 3.8 mm

Mounting Hole Diameter D (imperial) 0.12 "

Mounting Hole Diameter D (metric) 3.1 mm

Mounting Hole Centers (imperial) 0.52 "

Mounting Hole Centers (metric) 13.2 mm

## Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 10000 Pieces

Weight (Metric) 1.6 kg

## Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

**Adhesive** Acrylate with base of acrylic foam

**Shortcut Adhesive** mod. Acrylate

**Adhesive Operating Temperature** -40 °F to +194 °F (-40 °C to +90 °C)

**Flammability** UL94 V2 (excluding adhesive)

**Halogenfree** Yes

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes