

155-12300

Article Number: 155-12300

Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg

HellermannTyton



Base Data

Local Order Number 155-12300

Type T50SOSBS5E

Color Black (BK)

Features and Benefits

- Oval mount design pushes on easy by hand without the need for tools.
- Design provides low insertion and high extraction force.

Product Description The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Short Description Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225 N

Length L (imperial) 6.0 "

Length L (metric) 160.0 mm

Width W (imperial) 0.19 "

Width W (metric) 4.7 mm

Width W2 (imperial) 0.5 "

Width W2 (metric) 12.0 mm

Height H (imperial) 0.06 "

Height H (metric) 1.35 mm

Height H2 (imperial) 0.6 "

Height H2 (metric) 15 mm

Bundle Diameter min (imperial) 0.04 "

Bundle Diameter min (metric) 1.0 mm

Bundle Diameter max (imperial) 1.4 "

Bundle Diameter max (metric) 35.0 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.35 mm

Stud Size (Imperial) 0.2 "

Stud Size (Metric) 5.0 mm

Logistics and Packaging

Quantity per bag
Package Quantity 500
Carton Quantity 4000 Pieces
Weight (Metric) 2.85 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity Yes