## 596-00196

**Article Number: 596-00196**

**Insert for 596-00193, 1.06" X .59",, Plastic, Clear, 90/pkg**

✓ RoHS

## Base Data

| | |
|---|---|
| Local Order Number | 596-00196 |
| Type | TC15X67 |
| Color | Transparent (CL) |
| Features and Benefits | • The transparent covers are designed to snap easily into the legend base after the printed legend insert has been installed.<br>• The clear cover further serves to protect the printed legend for long term and durable identification of control panels, panel buttons and any industrial equipment. |
| Product Description | Plastic Nameplate labels are less costly than plastic or metal engraved plates, saving material costs. Plastic Nameplate labels are made of a UL94VO rated polycarbonate that can be mounted mechanically or using an adhesive backing. HellermannTyton thermal transfer or laser labels can be printed and applied to the inserts and covered with a clear plastic cover to protect printed text. |
| Self adhesive (Yes/No) | Yes |
| Short Description | Insert for 596-00193, 1.06" X .59",, Plastic, Clear, 90/pkg |

## Product Dimensions

| | |
|---|---|
| Width W (imperial) | 1.06 " |
| Width W (metric) | 27 mm |
| Height H (imperial) | 0.59 " |
| Height H (metric) | 15 mm |
| Horizontal Repeat HR (metric) | 27 mm |
| Horizontal Repeat HR (imperial) | 1.06 " |
| Print Method | Thermal Transfer |
| Vertical Repeat VR (imperial) | 0.59 " |
| Vertical Repeat VR (metric) | 15 mm |

## Logistics and Packaging

| | |
|---|---|
| Quantity per | pack |
| Package Quantity (imperial) | 90 |
| Package Quantity | 90 |

## Material and Specifications

| | |
|---|---|
| Material | Polycarbonate (PC) |
| Material Shortcut | PC |
| Flammability | UL94 V0 |
| Operating Temperature | -22 °F to +266 °F (-30 °C to +130 °C) |
| ROHS Conformity | Yes |