

HDM500BHIHSUVC2

Article Number: 151-00446

High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg



Base Data

Local Order Number	HDM500BHIHSUVC2
Type	HDM500
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Mount and tie combination makes it easy to service bundles in the field. • Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments. • Eliminates the needs for multiple sized fix diameter clamps.
Product Description	This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	High Torque Mount, Mounting Hole 0.5", Max Torque 114.0 lb - ft, PA66HIRHSUV, Black, 100/pkg

Product Dimensions

Length L (imperial)	1.9 "
Length L (metric)	47.0 mm
Width W (imperial)	1.0 "
Width W (metric)	25.0 mm
Cable Tie Width Max (imperial)	0.5 "
Cable Tie Width max. (metric)	12.7 mm
Mounting Hole Diameter D (imperial)	0.5 "
Mounting Hole Diameter D (metric)	12.7 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	500
Weight (Metric)	15.56 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Maximum Torque (kgf-cm)	1576 kgf-cm
Maximum Torque (lbf-ft)	114 lbf-ft
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes

