Smoke Alarm

First Alert®

ONELINK enabled alarms communicate with each other...

When **ONE** sounds ...they **ALL** sound

ONELINK™

EZ Access Battery Door

WIRELESS

FEATURES	BENEFITS
Wireless Installation	Wireless connect up to 18 Onelink alarms in the home and when one sounds they all sound
Battery Operated	2 AA batteries included - operates during power outages
Photoelectric Technology	Most sensitive to smoldering fires and reduces false alarms caused by cooking smoke and shower steam
EZ Access Battery Door	No need to remove alarm from the ceiling to change battery
Mute/Test & Low Battery Warning Silence	Mutes unwanted alarms immediately and also tests alarm function

Model Number: SA500A
Primary Packaging: Clamshell
Unit UPC: 0 29054 00172 6
Case Pack Qty: 3

Unit Dimensions: 10.4"H x 2.9"W x 7.2"L
Each Cube: 0.126 cubic feet
Each Weight: 0.8311 lbs.

Case UCC: 300 29054 00172 7
Case Dimensions: 10.4"H x 7.2"W x 8.7"L
Each Cube: 0.38 cubic feet
Each Weight: 2.5 lbs.

Pallet Pack Qty: 336
Cases Per Layer: 28
Pallet Tier: 4
Pallet Dimension: 47.1"H x 40"L x 48"W
Pallet Pack Cube: 52.33 cubic feet
Pallet Pack Weight: 279.2 lbs.

ETL
C US
INTERTEK
LISTED
In compliance with ULC

10 YEAR LIMITED WARRANTY

P PHOTOELECTRIC

Note: All First Alert smoke and CO alarms feature the EZ Access battery door. Dimensions and weight are subject to change.

CAT.
SA500CNA