



### Product Description

A highly concentrated formula that inhibits gelling & improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the proper ratios.

### Product Specifications

<b>Applications</b>	For use in diesel engines.
<b>Unit Package Description</b>	1 Quart Can
<b>Generic Description 1</b>	Premium Anti Gel with Lubricity
<b>Brand</b>	CRC
<b>Net Fill</b>	30 Fl Oz
<b>UPC Code</b>	078254056326
<b>Unit Dimensions</b>	10H x 1.63W x 4.5D in
<b>Units Per Case</b>	12
<b>Case Dimensions</b>	16.3H x 9W x 9.4D in
<b>Cases Per Pallet</b>	50
<b>Case Weight</b>	23 lbs
<b>I 2 of 5 Code</b>	30078254056327
<b>Appearance</b>	Amber Liquid
<b>Odor</b>	Aromatic
<b>Flashpoint</b>	87°F
<b>Flammability</b>	Flammable
<b>Specific Gravity</b>	0.88
<b>Plastic Safe</b>	No
<b>DOT Proper Shipping Name</b>	Consumer Commodity
<b>VOC % (Federal)</b>	95.4
<b>VOC g/L (Federal)</b>	838.7
<b>VOC Lbs./Gal. (Federal)</b>	7.0
<b>Compliant For CA</b>	Yes
<b>VOC Category</b>	Not Regulated
<b>Removal (How To)</b>	Remove with Petroleum Distillates.
<b>Treatment Ratio</b>	Preventative Maintenance: 1 Qt treats 500 Gal, Pre-existing Condition: 1 Qt treats 125 Gal