

05655 -- Diesel Cold Flow™ Anti-Gel with Lubricity, 55 Gal

**Product Description**

A highly concentrated formula that inhibits gelling & improves flowability of diesel fuel in cold weather. Lowers the pour point by as much as 40 F. when used in the proper ratios.

Product Specifications

Applications	For use in diesel engines.
Unit Package Description	55 Gallon Drum
Generic Description 1	Premium Anti Gel with Lubricity
Brand	CRC
Net Fill	55 Gal
UPC Code	078254056555
Unit Dimensions	35H x 24.5W x 24.5D in
Units Per Case	1
Case Dimensions	35H x 24.5W x 24.5D in
Cases Per Pallet	4
Case Weight	441 lbs
Appearance	Amber Liquid
Odor	Aromatic
Flashpoint	87°F
Flammability	Flammable
Specific Gravity	0.88
Plastic Safe	No
DOT Proper Shipping Name	Flammable Liquids, N.O.S. (Xylene & Petroleum Naphtha)
VOC % (Federal)	95.4
VOC g/L (Federal)	838.7
VOC Lbs./Gal. (Federal)	7.0
Compliant For CA	Yes
VOC Category	Not Regulated
Removal (How To)	Remove with Petroleum Distillates.
Treatment Ratio	Preventative Maintenance: 55 Gal treats 55000 Gal, Pre-existing Condition: 55 Gal treats 27500 Gal