SL2515 -- Soluble Oil, 5 Gal



Product Description

For use in most machine shop applications, particularly grinding. Use for improved wetting, cleaning & lubricating during metal cutting and grinding applications.

Product Specifications

Applications Cutting, grinding (30:2 - 50:1 water to oil),

grinding of ferrous metals, grinding of nonferrous metals, machining (10:1 - 30:1 water

to oil)

Unit Package Description 5 Gallon Pail

Brand Sta-Lube
Generic Description 1 Soluble Oil
Net Fill 5 Gal

 UPC Code
 072213251500

 Unit Dimensions
 14.5H x 12W x 12D in

Units Per Case 1

Case Dimensions 14.5H x 12W x 12D in

Cases Per Pallet36Case Weight43 lbsAppearanceAmber LiquidOdorFaint Petroleum

Flashpoint 350°F

Flammability Non-flammable

Specific Gravity 0.92 Plastic Safe Yes

Evaporation Rate <1 (butyl acetate=1)

ISO Viscosity Grade 20 to 30 NSF Registered No

DOT Proper Shipping Name Not Regulated

 VOC % (Federal)
 2.63

 VOC g/L (Federal)
 24.2

 VOC Lbs./Gal. (Federal)
 7.66

VOC Category Not Regulated