

SL3125 -- Marine Boat Trailer and 4x4 Wheel Bearing Grease, 35 Lbs**Product Description**

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.

Product Specifications**Applications**

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches

Unit Package Description

35 Pound Pail

Brand

Sta-Lube

Generic Description 1

Marine Grease for Boat Trailer

Net Fill

35 Lb

UPC Code

072213312508

Unit Dimensions

14.5H x 12W x 12D in

Units Per Case

1

Case Dimensions

14.5H x 12W x 12D in

Cases Per Pallet

36

Case Weight

41 lbs

Appearance

Blue Semi-Solid to Solid Grease

Odor

Faint Petroleum

Base Type

Aluminum Complex

Flashpoint

>450°F

Flammability

Non-flammable

Specific Gravity

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

Not Determined

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Working Temp

0 to 325°F

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

500°F

Leakage

5

Low Temp Torque

Not Determined

Oil Separation

<10%

Oxidation Stability

5

Pour Point

0°F

ISO Viscosity Grade

180

Water Washout

5

Worked Penetration

265 to 295

Propellant

None

NSF Registered

No

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

0

VOC g/L (Federal)

0

VOC Lbs./Gal. (Federal)

0

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.