

## SL3127 -- Marine Boat Trailer and 4x4 Wheel Bearing Grease, 120 Lbs

**Product Description**

A blue tacky, aluminum complex grease using a highly refined base oil. It has been formulated with a polymer to provide adhesive, non-blend and water wash-out characteristics. Will resist water under the most severe water conditions.

**Product Specifications****Applications**

Anti-friction bearings, blocks, boat trailer bearings, deck equipment, marine equipment, shaft log seals, sleeve bearings, slides, steering cables, steering dockside machinery, steering quadrants, turnbuckles, wheel bearings, winches

**Unit Package Description**

120 Pound Keg

**Brand**

Sta-Lube

**Generic Description 1**

Marine Grease for Boat Trailer

**Net Fill**

120 Lb

**UPC Code**

072213312706

**Unit Dimensions**

26.88H x 14.65W x 14.65D in

**Units Per Case**

1

**Case Dimensions**

26.88H x 14.65W x 14.65D in

**Cases Per Pallet**

9

**Case Weight**

130 lbs

**I 2 of 5 Code**

30072213312707

**Appearance**

Blue Semi-Solid to Solid Grease

**Odor**

Faint Petroleum

**Base Type**

Aluminum Complex

**Flashpoint**

>450°F

**Flammability**

Non-flammable

**Specific Gravity**

0.9 at 60°F

**NLGI Grade**

2

**Timken OK Load [Lbs.]**

Not Determined

**Plastic Safe**

Not Determined

**Evaporation Rate**

<0.01 (Butyl Acetate=1)

**Working Temp**

0 to 325°F

**4 Ball EP**

Not Determined

**4 Ball Wear**

Not Determined

**Drop Point**

500°F

**Leakage**

5

**Low Temp Torque**

Not Determined

**Oil Separation**

<10%

**Oxidation Stability**

5

**Pour Point**

0°F

**ISO Viscosity Grade**

180

**Water Washout**

5

**Worked Penetration**

265 to 295

**Propellant**

None

**NSF Registered**

No

**DOT Proper Shipping Name**

Not Regulated

**VOC % (Federal)**

0

**VOC g/L (Federal)**

0

**VOC Lbs./Gal. (Federal)**

0

**VOC Category**

Not Regulated

**Removal (How To)**

Remove with a degreaser or brake cleaner product.