

**SL3136 -- Heavy Duty Drum Brake Wheel Bearing Grease, 7 Lbs**

No Photo  
Available

**Product Description**

A sodium-based short fiber grease for autos & trucks with drum brake systems and slow speed industrial bearings. Meets demands for most economical wheel bearing lubrication. Good adhesive characteristics.

**Product Specifications**

<b>Applications</b>	Drum brake systems, for use where heavy loads & slow speeds are present
<b>Unit Package Description</b>	7 Pound Pail
<b>Brand</b>	Sta-Lube
<b>Generic Description 1</b>	HD Drum Brake Wheel Bearing Grease
<b>Net Fill</b>	7 Lb
<b>UPC Code</b>	072213313604
<b>Unit Dimensions</b>	7.75H x 7.5W x 7.5D in
<b>Units Per Case</b>	4
<b>Case Dimensions</b>	8H x 16.5W x 16.5D in
<b>Cases Per Pallet</b>	54
<b>Case Weight</b>	33 lbs
<b>I 2 of 5 Code</b>	30072213313605
<b>Appearance</b>	Amber Semi-Solid to Solid Grease
<b>Odor</b>	Faint Petroleum
<b>Base Type</b>	Sodium
<b>Flashpoint</b>	>450°F
<b>Flammability</b>	Non-flammable
<b>Specific Gravity</b>	0.9 at 60°F
<b>NLGI Grade</b>	2.5
<b>Timken OK Load [Lbs.]</b>	Not Determined
<b>Plastic Safe</b>	Not Determined
<b>Evaporation Rate</b>	<0.01 (Butyl Acetate=1)
<b>Working Temp</b>	10 to 250°F
<b>4 Ball Wear</b>	Not Determined
<b>Drop Point</b>	360°F
<b>Leakage</b>	Not Determined
<b>Low Temp Torque</b>	Not Determined
<b>Oil Separation</b>	<10
<b>Oxidation Stability</b>	5 Lbs
<b>Pour Point</b>	0°F (oil)
<b>ISO Viscosity Grade</b>	190
<b>Worked Penetration</b>	240 to 260
<b>Propellant</b>	None
<b>NSF Registered</b>	No
<b>DOT Proper Shipping Name</b>	Not Regulated
<b>VOC % (Federal)</b>	0
<b>VOC g/L (Federal)</b>	0
<b>VOC Lbs./Gal. (Federal)</b>	0
<b>VOC Category</b>	Not Regulated
<b>Removal (How To)</b>	Remove with a degreaser or brake cleaner product.