

## SL3165 -- Hi Temperature Disc Brake Wheel Bearing Grease, 35 Lbs

**Product Description**

A very stable resistant Aluminum Complex grease. Contains rust & oxidation inhibitors, anti-wear and extreme pressure additives & fortified with "moly" and graphite. For use in automotive disc/drum brakes, chassis and suspension systems

**Product Specifications****Applications**

Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings

**Unit Package Description**

35 Pound Pail

**Brand**

Sta-Lube

**Generic Description 1**

Hi-Temp Disc Brake Wheel Grease

**Net Fill**

35 Lb

**UPC Code**

072213316506

**Unit Dimensions**

14.5H x 12W x 12D in

**Units Per Case**

1

**Case Dimensions**

14.5H x 12W x 12D in

**Cases Per Pallet**

36

**Case Weight**

40 lbs

**Appearance**

Black Semi-Solid to Solid Grease

**Odor**

Faint Petroleum

**Base Type**

Lithium Complex

**Flashpoint**

>450°F

**Flammability**

Non-flammable

**Specific Gravity**

0.9 at 60°F

**NLGI Grade**

2

**Timken OK Load [Lbs.]**

60 Lbs

**Plastic Safe**

Not Determined

**Evaporation Rate**

<0.01 (Butyl Acetate=1)

**Working Temp**

0 to 325°F

**4 Ball EP**

315 Kg Weld,30 LWI

**4 Ball Wear**

0.75 mm

**Drop Point**

500°F

**Elastomer Compatibility**

0 to 30% vol; 0 to 15 hard

**Leakage**

10g Max

**Low Temp Torque**

15.5 Max

**Oil Separation**

<10%

**Oxidation Stability**

2 to 3

**Pour Point**

0°F

**ISO Viscosity Grade**

205

**Water Washout**

<15%

**Worked Penetration**

265 to 295

**Propellant**

None

**NSF Registered**

No

**DOT Proper Shipping Name**

Not Regulated

**VOC % (Federal)**

0.4

**VOC g/L (Federal)**

3.6

**VOC Lbs./Gal. (Federal)**

0.03

**VOC Category**

Not Regulated

**Removal (How To)**

Remove with a degreaser or brake cleaner product.