

SL3166 -- Hi Temperature Disc Brake Wheel Bearing Grease, 7 Lbs

**Product Description**

A very stable resistant Aluminum Complex grease. Contains rust & oxidation inhibitors, anti-wear and extreme pressure additives & fortified with "moly" and graphite. For use in automotive disc/drum brakes, chassis and suspension systems

Product Specifications**Applications**

Automotive applications, ball joints, bearings, chassis points, construction ball & roller bearings, conveyor bearings, disc-brake systems, farm equipment, guides, mining applications, press rolls, roller bearings, slides, wheel bearings

Unit Package Description

7 Pound Pail

Brand

Sta-Lube

Generic Description 1

Hi-Temp Disc Brake Wheel Grease

Net Fill

7 Lb

UPC Code

072213316605

Unit Dimensions

7.75H x 7.5W x 7.5D in

Units Per Case

4

Case Dimensions

8H x 16.5W x 16.5D in

Cases Per Pallet

54

Case Weight

33 lbs

I 2 of 5 Code

30072213316606

Appearance

Black Semi-Solid to Solid Grease

Odor

Faint Petroleum

Base Type

Lithium Complex

Flashpoint

>450°F

Flammability

Non-flammable

Specific Gravity

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

60 Lbs

Plastic Safe

Not Determined

Evaporation Rate

<0.01 (Butyl Acetate=1)

Working Temp

0 to 325°F

4 Ball EP

315 Kg Weld,30 LWI

4 Ball Wear

0.75 mm

Drop Point

500°F

Elastomer Compatibility

0 to 30% vol; 0 to 15 hard

Leakage

10g Max

Low Temp Torque

15.5 Max

Oil Separation

<10%

Oxidation Stability

2 to 3

Pour Point

0°F

ISO Viscosity Grade

205

Water Washout

<15%

Worked Penetration

265 to 295

Propellant

None

NSF Registered

No

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

0.4

VOC g/L (Federal)

3.6

VOC Lbs./Gal. (Federal)

0.03

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.