

SL3197 -- Sta-Plex™ Extreme Pressure Premium Red Grease, 120 lbs

**Product Description**

A superior multi-purpose certified lithium complex based NLGI #2 grease. Contains extreme pressure, anti-wear, & anti-oxidation additives. Ideal for high temperature & performance applications. Drop point 500°F

Product Specifications**Applications**

Ind. mining, metal production, machining, plastic molding, pumps, electric motors, ball & roller bearings, kilns, assembly plants, drying ovens, trucks, automobiles, buses, construction equipment, off-road operations, tractors mowers, reapers, water pumps

Unit Package Description

120 Pound Keg

Brand

Sta-Lube

Generic Description 1

Premium Red Grease

Net Fill

120 Lb

UPC Code

072213319705

Unit Dimensions

26.88H x 14.65W x 14.65D in

Units Per Case

1

Case Dimensions

26.88H x 14.65W x 14.65D in

Cases Per Pallet

9

Case Weight

130 lbs

Appearance

Red Semi-Solid to Solid Grease

Odor

Faint Petroleum

Base Type

Lithium Complex

Flashpoint

475°F

Flammability

Non-flammable

Specific Gravity

0.9 at 60°F

NLGI Grade

2

Timken OK Load [Lbs.]

60 Lbs Min

Plastic Safe

Not Determined

Evaporation Rate

<1 (butyl acetate=1)

Working Temp

0 to 400°F (300°F continuous)

4 Ball EP

77 LWI, 400 Kg Weld

4 Ball Wear

0.4 typical; 0.6 Max

Drop Point

500+ °F

Elastomer Compatibility

0 to 30% vol; 0 to 15 hard

Leakage

4g

Low Temp Torque

15.5 Max

Oil Separation

5% Typical

Oxidation Stability

5

Pour Point

5°F

ISO Viscosity Grade

230

Water Washout

5% typical

Worked Penetration

265 to 295

Propellant

None

NSF Category Code

H2

NSF Registered

Yes

NSF Number

145511

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

1

VOC g/L (Federal)

9

VOC Lbs./Gal. (Federal)

0.075

VOC Category

Not Regulated

Removal (How To)

Remove with a degreaser or brake cleaner product.