



# Energy Advantage IR PAR30

## Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

### Product data

General Information	
Cap-Base	E26 [ Single Contact Medium Screw]
Operating Position	Universal [ Universal]
Main Application	Flood and Ambient Lighting
Gas Filling	GAS
Life with 3 Hour Per Day Use	3.8 a

Light Technical	
Beam Angle (Nom)	25 °
Initial lumen (Nom)	1020 lm
Luminous Intensity (Nom)	3300 cd
Beam Description	Flood [ Flood]
Correlated Color Temperature (Nom)	2760 K
Color Rendering Index (Nom)	100

Operating and Electrical	
Power (Rated) (Nom)	55 W
Voltage (Nom)	120 V

Mechanical and Housing	
Bulb Finish	Clear (CL)

Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [ Axial]


Approval and Application	
Estimated Energy Cost Per Year	6.62 \$

Product Data	
Order product name	Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1
EAN/UPC - Product	046677238568
Order code	238568
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	15
Material Nr. (12NC)	924757122501
Net Weight (Piece)	190.000 g

# Energy Advantage IR PAR30

## Dimensional drawing

Product	D	C (max)
Energy Advantage IR 55PAR30S/IRC+/FL25 120V 15/1	3.75 in	3.625 in



PAR30 IRC 55W E26/Brass 120V FL 25D CC-8

