



Core & Coil (71A) MH 175W - 450W

CORE & COIL HID 71A5791500D

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

Product data

General Information		
ANSI Code	M58	
Lamp Type	250W MH	
Number Of Lamps	1 piece/unit	
Circuit Type	CWA	
Ballast Type	Magnetic HID	
Base Model	71A5791	
Core Size	3 X 4 (2 coil)	
Suitable For Outdoor Use	Yes	
Ignitor Catalog Number	NA	
Ignitor Temperature Rating	NA	
Capacitor Value	15 MFD	
Capacitor Catalog Number	7C150P40R	
Capacitor Requirements	400V	
Capacitor Temperature Rating	105°C	
Capacitor Diameter/Oval Dimensions	1.75 in	
Capacitor Height	3.75 in	
Automatic Restart	No	


Operating and Electrical	
Input Voltage	120/208/240/277 V
Input Frequency	60 Hz
Power (Rated) (Nom)	250 W
Input Current (Open Circuit)	2.6/1.5/1.3/1.1 A
Input Current (Starting)	1/0.6/0.5/0.45 A
Input Current (Short Circuit)	1.2-1.8/0.7-1/0.6-0.9/0.5-0.75 A
Secondary Short Circuit Current	2-3 A
Constant Wattage Deviation	8%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	300 V
Input Current (Nom)	2.6/1.5/1.3/1.1 A A
Input Power (Nom)	294 W
Rated Lamp Power	250W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded

Core & Coil (71A) MH 175W - 450W

Remote Wiring Configuration Allowed	Yes	
Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used	
Recommended Fuse Value	8/5/5/3 A	
Approval and Application		
Open Circuit Voltage Test (Volts)	270-330 V	
Approval Marks	ULR CSA certificate RoHS Compliant	
Temperature Marking	C/C/D/D	
UL Recognized	Yes	
Hipot Test (1 Minute)	2000 V	
Hipot Test (2 Seconds)	2500 V	
UL Insulation Class	H(180°C)	

UL Temperature Code	1029D
Product Data	
Order product name	CORE & COIL HID 71A5791500D
EAN/UPC - Product	781087099599
Order code	913700509311
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913700509311
Net Weight (Piece)	4.296 kg

Dimensional drawing



MH BAL 250W M58 QUAD C&C





© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, February 1 - data subject to change