



Val-U-Pak Plus (77L)

CORE & COIL HID 77L6051001D

Our VAL-U-PAK Plus magnetic HID replacement kits assemble the required components — including lamp, core and coil, the appropriate capacitor, ignitor (where required), mounting bracket and hardware, and instructions — in one convenient package. This saves valuable time for MRO and contractor applications.

Product data

General Information			
ANSI Code	M59		
Lamp Type	400W MH		
Number Of Lamps	1 piece/unit		
Circuit Type	CWA		
Ballast Type	Magnetic HID		
Base Model	71A6051		
Core Size	4 1/4 x 4 3/4 (2 coil)		
Suitable For Outdoor Use	Yes		
Ignitor Catalog Number	NA		
Ignitor Temperature Rating	NA		
Capacitor Value	24 MFD		
Capacitor Catalog Number	7C240P40R		
Capacitor Requirements	400V		
Capacitor Temperature Rating	105°C		
Capacitor Diameter/Oval Dimensions	1.75 in		
Capacitor Height	4.8 in		
Automatic Restart	No		
Operating and Electrical			
Input Voltage	120/208/240/277/480 V		
Input Frequency	60 Hz		

Power (Rated) (Nom)	400 W
Input Current (Open Circuit)	2.86/1.45/1.29/1.1/0.62 A
Input Current (Starting)	3.51/2.0/1.72/1.49/0.86 A
Input Current (Short Circuit)	2.7-4.05/1.56-2.34/1.29-1.92/1.17-1.76/0.68-1.02 A
Secondary Short Circuit Current	3.04-4.56 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	300 V
Input Current (Nom)	4.13/2.29/2.2/1.72/0.99 A A
Input Power (Nom)	455 W
Rated Lamp Power	400W W
Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	Determined by AWG used
Recommended Fuse Value	10/7/5/5/3 A


Datasheet, 2016, December 22 data subject to change

Val-U-Pak Plus (77L)

rature Marking ULR CSA certificate RoHS Compl C/C/D/C/D	Approval and Application	
rature Marking C/C/D/C/D	Open Circuit Voltage Test (Volts)	280-320 V
	Approval Marks	ULR CSA certificate RoHS Compliant
	Temperature Marking	C/C/D/C/D
ognized res	UL Recognized	Yes
Test (1 Minute) 2000 V	Hipot Test (1 Minute)	2000 V
Test (2 Seconds) 2500 V	Hipot Test (2 Seconds)	2500 V
ulation Class H(180°C)	UL Insulation Class	H(180°C)
nperature Code 1029D	UL Temperature Code	1029D

Product Data	
Order product name	CORE & COIL HID 77L6051001D
EAN/UPC - Product	781087114247
Order code	913710416301
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	913710416301
Net Weight (Piece)	7.213 kg

Dimensional drawing



MH BAL 400W M59 5-TAP KIT WITH LAMP

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 77L6051001D	4.45 in	2.34 in	4.8 in	4.4 in	4.3 in	3.9 in

