

# Core & Coil (71A) MH ~LT~ 175W

## CORE & COIL HID 71A5442500DT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

### Product data

General Information	
ANSI Code	M102-M142
Lamp Type	150 MH
Number Of Lamps	1 piece/unit
Circuit Type	HX-HPF
Ballast Type	Magnetic HID
Base Model	71A5442T
Core Size	3 X 4 (2 coil)
Suitable For Outdoor Use	Yes
Ignitor Catalog Number	LI533-H4
Ignitor Temperature Rating	105°C
Capacitor Value	16 MFD
Capacitor Catalog Number	7C160M30RA
Capacitor Requirements	280V
Capacitor Temperature Rating	105°C
Capacitor Diameter/Oval Dimensions	1.65 in
Capacitor Height	2.75 in
Automatic Restart	No

Operating and Electrical	
Input Voltage	480 V
Input Frequency	60 Hz
Power (Rated) (Nom)	150 W
Input Current (Open Circuit)	0.81 A
Input Current (Starting)	0.45 A
Input Current (Short Circuit)	0.33-0.49 A
Secondary Short Circuit Current	1.91-2.33 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	270 V
Input Current (Nom)	0.42 A A
Input Power (Nom)	185 W
Rated Lamp Power	150W W

Wiring	
Wire Striplength	0.5 mm
Wire Length By Color	12"
Wire Type	Stranded

## Core & Coil (71A) MH ~LT~ 175W

Remote Wiring Configuration Allowed	Yes
Max Ballast-Lamp Distance Remote Wiring	10'
Recommended Fuse Value	3 A

### Approval and Application


Open Circuit Voltage Test (Volts)	243-297 V
Approval Marks	ULR CSA certificate RoHS Compliant
Temperature Marking	B
UL Recognized	Yes
Hipot Test (1 Minute)	2000 V
Hipot Test (2 Seconds)	2500 V
UL Insulation Class	H(180°C)

UL Temperature Code	1029B
---------------------	-------

### Product Data

Order product name	CORE & COIL HID 71A5442500DT
EAN/UPC - Product	781087026335
Order code	913710491402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	913710491402
Net Weight (Piece)	4.078 kg

### Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A5442500DT	3.92 in	2.8 in	3.9 in	3.5 in	2.8 in	2.4 in

MH BAL 150W M102/142 480V/120T C&C

