



Mark 10 Powerline

MARK 10 POWERLINE ELE DIM BALLAST (2) 42W CFL (4-PIN) 277V

For companies looking to make their fixed-output linear T8, 4-pin CFL, and T5/HO fluorescent systems more cost effective and sustainable, Mark 10 Powerline ballasts provide an easy solution without the need for additional control leads. Simply, (1) replace the ballast, (2) replace the switch, (3) dim the lights, that is all it takes. It's that easy to bring the convenience and flexibility of fluorescent dimming to conference rooms, private offices, auditoriums, architectural cove lighting – anywhere dimming is required.

Product data

General Information				
Lamp Type	CFTR42W/GX24Q			
Number of Lamps	2 piece/unit			
Ballast Type	Dimmable Fluorescent			
Base Model	VEZ2T42M3LD			
Suitable For Outdoor Use	Yes			
Automatic Restart	Yes			
Operating and Electrical				
Input Voltage	277 V			
Input Frequency	60 Hz			
Max THD	10 %			
Power (Rated) (Nom)	42 W			
Starting Method	Programmed Start			
Lamp Current Crest Factor (Nom)	1.6			
Ignition Time (Nom)	1.5 s			
Ballast Factor (Max)	1			
Ballast Factor (Min)	0.05			
Power Factor (Nom)	0.98			

0.36 A	
98 W	
20 W	
42W W	
BLK & WHT	
RED, YEL & BLU	
0.375 mm	
NA	
Series	
No wires	
18AWG mm	
Solid	
No	
No	
No	
No Remote	
No Tandem	


Datasheet, 2016, February 1 data subject to change

Mark 10 Powerline

Max Ballast-Lamp Distance Through Wiring	No Through			
Connector Type	Poke-In			
Temperature				
T-Case Maximum (Nom)	70 °C			
Mechanical and Housing				
Housing Material	Metal			
Housing	M3			
Housing Dimensions	6.28" x 3.0" x 1.29"			
Approval and Application				
EMC Immunity Standard	FCC Consumer			

Sound Rating	A No			
UL Recognized				
Product Data				
Order product name	MARK 10 POWERLINE VEZ2T42M3LD35M			
EAN/UPC - Product	781087114643			
Order code	VEZ2T42M3LD35M			
Numerator - Quantity Per Pack	1			
Numerator - Packs per outer box	20			
Material Nr. (12NC)	913700501521			
Net Weight (Piece)	441.000 g			

Dimensional drawing



ELE DIM BALLAST (2) 42W CFL (4-PIN) 277V

Product	A1	A2	B1	C1
MARK 10 POWERLINE VEZ2T42M3LD35M	6.0 in	5.5 in	3.00 in	1.29 in

