



# Core & Coil (71A) HPS 200W - 400W

## CORE & COIL HID HPS BAL 200W S66 QUAD KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	S66			
Lamp Type	200W HPS			
Number of Lamps	1 piece/unit			
Circuit Type	CWA			
Ballast Type	Magnetic HID			
Base Model	71A8970			
Core Size	4 x 4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI501-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	28 MFD			
Capacitor Catalog Number	7C280P30RA			
Capacitor Requirements	280V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.85 in			
Capacitor Height	3.7 in			
Automatic Restart	No			

Operating and Electrical			
Input Voltage	120/208/240/277 V		
Input Frequency	60 Hz		
Power (Rated) (Nom)	200 W		
Inp. Current (Open Circuit)	1.3/0.75/0.65/0.6 A		
Input Current (Starting)	1.5/0.9/0.75/0.65 A		
Input Current (Short Circuit)	1-1.6/0.6-0.95/0.5-0.8/0.45-0.7 A		
Secondary Short Circuit Current	2.8-3.4 A		
Constant Wattage Deviation	Within Trapezoid		
Ballast Factor (Nom)	1		
Power Factor (Nom)	0.90		
Nominal Open Circuit Voltage	185 V		
Input Current (Operating) (Nom)	2.22/1.28/1.11/0.96 A A		
Input Power (Nom)	240 W		
Rated Lamp Watts	200W W		
Wiring			
Wire Striplength	0.5 mm		
Wire Length By Color	12"		
Wire Type	Stranded		


Datasheet, 2016, February 1 data subject to change

# Core & Coil (71A) HPS 200W - 400W

Remote Wiring Configuration Allowed	Yes		
Max Ballast-Lamp Distance Remote Wiring	2'		
Recommended Fuse Value	6/4/3/3 A		
Approval and Application			
Open Circuit Voltage Test (Volts)	165-205 V		
Approbation Marks	ULR CSA certificate RoHS Compliant		
Temperature Marking	E/D/D/D		
UL Recognized	Yes		
Hipot Test (1 Minute)	2000 V		
Hipot Test (2 Seconds)	2500 V		
UL Insulation Class	H(180°C)		

UL Temperature Code	1029E		
Product Data			
Order product name	CORE & COIL HID 71A8970001D		
EAN/UPC - Product	781087897010		
Order code	71A8970001D		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	913700540509		
Net Weight (Piece)	4.233 kg		

### Dimensional drawing



Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A8970001D	3 in	1.2 in	4.8 in	4.4 in	4.3 in	3.9 in

