



## Core & Coil (71A) MH 175W - 450W

# CORE & COIL HID MH BAL 400W M135/155 480V/120T KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information				
ANSI Code	M135-M155			
Lamp Type	400W MH			
Number of Lamps	1 piece/unit			
Circuit Type	SUPER-CWA			
Ballast Type	Magnetic HID			
Base Model	71A6042TA			
Core Size	4 1/4 x 4 3/4 (2 coil)			
Suitable For Outdoor Use	Yes			
Ignitor Catalog Number	LI533-H4			
Ignitor Temperature Rating	105°C			
Capacitor Value	26 MFD			
Capacitor Catalog Number	7C260P33R			
Capacitor Requirements	330V			
Capacitor Temperature Rating	105°C			
Capacitor Diameter/Oval Dimensions	1.75 in			
Capacitor Height	4.8 in			
Automatic Restart	No			

Operating and Electrical		
Input Voltage	480/120T V	
Input Frequency	60 Hz	
Power (Rated) (Nom)	400 W	
Inp. Current (Open Circuit)	0.7 A	
Input Current (Starting)	0.75 A	
Input Current (Short Circuit)	0.5-0.8 A	
Secondary Short Circuit Current	3.6-4.4 A	
Constant Wattage Deviation	10%	
Ballast Factor (Nom)	1	
Power Factor (Nom)	0.90	
Nominal Open Circuit Voltage	270 V	
Input Current (Operating) (Nom)	1 A A	
Input Power (Nom)	452 W	
Rated Lamp Watts	400W W	
Wiring		
Wire Striplength	0.5 mm	
Wire Length By Color	12"	-


Datasheet, 2015, November 29 data subject to change

### Core & Coil (71A) MH 175W - 450W

Wire Type	Stranded			
Remote Wiring Configuration Allowed	Yes			
Max Ballast-Lamp Distance Remote Wiring	2'			
Recommended Fuse Value	3 A			
Approval and Application				
Open Circuit Voltage Test (Volts)	240-300 V			
Approbation Marks	ULR CSA certificate RoHS Compliant			
Temperature Marking	D			
UL Recognized	Yes			
Hipot Test (1 Minute)	2000 V			
Hipot Test (2 Seconds)	2500 V			
UL Insulation Class	H(180°C)			

UL Temperature Code	1029D		
ou romporataro ocuo	10205		
Product Data			
Order product name	CORE & COIL HID 71A6042001D		
EAN/UPC - Product	781087082638		
Order code	71A6042001D		
Local order code	505172		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	913701135502		
Net Weight (Piece)	5.856 kg		

### **Dimensional drawing**



MH BAL 400W M135/155 480V/120T KIT

Product	C1	C2	A1	A2	B1	B2
CORE & COIL HID 71A6042001D	3.9 in	2.11 in	4.8 in	4.4 in	4.3 in	3.9 in

