



CONNECTION CABLE; LENGTH 1,0M; ROUND; CONNECTION OF BASIC UNIT TO CURRENT MEASURING MODULE, CURRENT/VOLTAGE MEASUR. MODULE, OPERATOR PANEL OR TO EXPANSION MODULES VIA SYSTEM INTERFACE

General technical data:	
product brand name	SIRIUS
Product designation	connecting cable
Design of the product	<kein Wert>
Protection class IP	<kein Wert>
Ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	<kein Wert>
Equipment marking acc. to DIN EN 61346-2	<kein Wert>
Certificates/ approvals:	

General Product Approval	EMC	Test Certificates
--------------------------	-----	-------------------



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



other

[Confirmation](#)

[PROFINET-Certification](#)



[PROFISafe-Certification](#)

Profibus

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3UF79370BA000>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79370BA000>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3UF79370BA000&lang=en

