

Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 45 mm Bar thickness: 5.10 mm+TT profile with 1 DIN rail 35 mm For 3RA6 compact load feeder Length 200 mm; Ue 690 V, IE up to 32 A, Notice: if rated current >12 A and short-circuit current > 25 kA max. conductor cross-section 6 mm<sup>2</sup> and minimum conductor length 2 m must be observed



Model	
Product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Current / at AC / rated value	32 A
Operating voltage / at AC / rated value	690 V
Width	45 mm
Busbar center-to-center spacing	60 mm
Net weight	315 g

General Product Approval				Declaration of Conformity	Test Certificates
 CSA	 UR	 UL		 EG-Konf.	<a href="#">Special Test Certificate</a>

Test Certificates	Shipping Approval				
<a href="#">Miscellaneous</a>	 BUREAU VERITAS	 LRS	 PRS	 RINA	 RMRS

other
<a href="#">Miscellaneous</a>

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1211-1NS10>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8US1211-1NS10>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1211-1NS10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1211-1NS10)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>