



busbar adapter 60 mm SYS. UL 508 Busbar system 60 mm Bar thickness: TT profile Can be used in spring circuits for 3VL circuit breaker with pipe contacting for cable outlet top/bottom Adapter length 190 mm Adapter width 105 mm for VL150X UL, CG FRAME UL rating 240-600V/150A IEC rating 690 V/160 A



Model	
Product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Current / at AC / rated value	160 A
Operating voltage / at AC / rated value	690 V
Width	105 mm
Busbar center-to-center spacing	60 mm
Net weight	968 g

General Product Approval				Declaration of Conformity	Test Certificates
 CSA	 UR	 UL		 EG-Konf.	Special Test Certificate

Test Certificates	Shipping Approval	other
Miscellaneous	 PRS	 RINA
		Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1213-4AQ01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1213-4AQ01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1213-4AQ01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

