







Busbar system Busbar center-to-center spacing 60 mm Device adapter, Width: 55 mm Bar thickness: 5.10 mm+TT profile for contactor with overload relay 3R, S2 with 1 DIN rail 35 mm, up to 56 A Length 182 mm



Model	
Product brand name	SENTRON
Product designation	Device adapter
Design of the product	Accessories
Current / at AC / rated value	56 A
Operating voltage / at AC / rated value	690 V
Width	55 mm
Busbar center-to-center spacing	60 mm
Net weight	232 g

General Product Approval			Declaration of Conformity	Test Certificates	
 CSA	 UR		 EG-Konf.	<a href="#">Special Test Certificate</a>	<a href="#">Miscellaneous</a>

Shipping Approval	other
 PRS	 RINA
	<a href="#">Miscellaneous</a>

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1261-5FM08>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8US1261-5FM08>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1261-5FM08](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1261-5FM08)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

