

## January 2015 NEW PRODUCTS AVAILABLE





Catalog Number	Trade Size	Lug Wire Size
162-G	3/4"	14 - 4
163-G	1"	14 - 4
164-G	1-1/4"	14 - 1/0
165-G	1-1/2"	14 - 1/0
166-G	2"	14 - 1/0
167-G	2-1/2"	14 - 1/0
168-G	3"	14 - 1/0
169-G	3-1/2"	6 - 3/0
170-G	4"	6 - 3/0

Material:

Zinc Die Cast Locknut Body Tin Plated Aluminum Alloy Lug



Listed to UL 514B and CSA C22.2 18.3-04

## **Grounding Locknuts**

Bridgeport now offers Grounding Locknuts from 3/4" to 4" Trade Sizes. These versatile locknuts are ETL Listed for use with all of Bridgeport Fittings' EMT and Rigid connectors, as well as threaded Rigid/IMC conduit.

Bridgeport's grounding locknuts provide a secure connection to the enclosure, and 3 tapped holes for proper placement of the ground lug. When thread length is limited, these can be used in place of a grounding bushing and standard locknut. Simply remove the standard locknut and thread on the grounding locknut.

Bridgeport's problem-solving grounding locknuts are not just for threaded hubs anymore. Also suitable for Service Entrance Equipment.

















