

Bridgeport Fittings Inc.


705 Lordship Blvd. Stratford, CT 06615

Phone: 203-377-5944 Fax: 203-381-3488

Hub Type

Images





Dimension A in Inches: 3.095 Dimension B in Inches: 3.200 Dimension C in Inches: 1.237 Dimension D in Inches: .565

Application

The MCH-200 is listed for use in wet and dry locations as a connector for rigid metal conduit or EMT with a Bridgeport Fittings connector. The MCH-200 will provide a wet locations seal. Rigid Metallic raceways which contain Ground Electrode Conductors (G.E.C.) are required to be bonded at the enclosure and where the conductor exits the raceway for attachment to the ground electrode. The MCH-200 can be used in both applications: at the enclosure and at the end of the bonding conductor raceway. Also Suitable for Direct Burial. Conductor Range 350 to 600 MCM Str. CU. Patented.

Product Information

Material: Stainless Steel

Certifications & Codes:

Federal

Specificatio A-A-50553A

n Number:

NEMA

FB-1

Standard:

UL File
Number:

Listed ETL under Bridgeport Fittings:
MCH-200. Conforms to UL 467 and

CSA C22.2 No. 18.3

UL 467

Standard:

UNSPSC: 39121613

Patent Number:

8,410,378; D703,519

Catalog ID: MCH-200

UPC Number: 78174702349

Description: 2" Stainless Steel Alloy grounding fitting with stainless steel set screws and Stainless steel locknut Buna

N sealing ring. NPT threads

Application: The MCH-200 is listed for use in wet and dry locations as a connector for rigid metal conduit or EMT with a Bridgeport Fittings connector. The MCH-200 will provide a wet locations seal. Rigid Metallic raceways which contain Ground Electrode Conductors (G.E.C.) are required to be bonded at the enclosure and where the conductor exits the raceway for attachment to the ground electrode. The MCH-200 can be used in both applications: at the enclosure and at the end of the bonding conductor raceway. Also Suitable for Direct Burial. Conductor Range 350 to 600 MCM Str. CU. Patented.

Trade Size: 2"

Std Pkg Qty: 10

Unit Qty: 1