

# The ultimate in corrosion resistance and durability

Eaton's Crouse-Hinds 316 stainless junction box is designed to provide long, dependable service in the most demanding environmental conditions. With four drilled and tapped conduit entries and pendant fixture cover or flat blank cover, the box provides versatility for mounting luminaires or terminating or splicing electrical circuits.

### Applications:

For use where high quality durable products that withstand corrosion, chemical treatments, and wash-downs are required, including:

- Wastewater treatment plants
- Food and beverage facilities
- Pharmaceutical plants
- Pulp and paper mills
- Mines

VXF stainless steel outlet boxes are installed in threaded rigid conduit systems to:

- Act as junction boxes for making terminations
- Act as pull outlets

### Certifications & Compliances:

- UL / cUL Listed File No. E15022
- NEC/CEC
  - Class I Div 2
  - Class II Div 1 & 2
  - Class III
- Fixture rated (with pendant cover)
- UL514A
- Wet Location
- NEMA 4X
- Assembled in the USA

### Standard Materials:

- Body, plugs and cover - 316 stainless steel
- Nuts and washers - stainless steel
- Gasket - neoprene

### Standard Finishes:

- Body, plugs, nuts and washer - natural
- GRF10SS - natural with #4 brushed finish



Universal box and 2 cover options for versatility and reliability in demanding conditions

## Ordering Information and Features:

### VXF Junction Box

Includes:

- (4) tapped conduit openings with (3) 316 stainless steel installed recessed hex plugs
- (4) 1/4-20 x 1" stainless steel hex head bolts for mounting box to surface
- (1) 10-32 x 1/4" installed green ground screw with slotted head



Cat. #	Description
VXF20SS	3/4" X Style Junction
VXF30SS	1" X Style Junction

### VXF Pendant Cover

Includes:

- Fixture rated up to 130 lbs. with VXF body
- Neoprene gasket
- (4) 1/4-20 x 5/8" stainless steel hex head bolts and lock washer for cover attachment to box
- (1) 10-24 x 5/8" phillips pan head set screw




Cat. #	Description
VXF12SS	3/4" Pendant Cover with Gasket

### VXF Blank Cover

Includes:

- Neoprene gasket
- (4) 1/4-20 x 5/8" stainless steel hex head bolts for cover attachment to box
- GRF10SS comes with PVC protective peel off coating



Cat. #	Description
GRF10SS	Flat Cover with Gasket



**Crouse-Hinds**  
by **EATON**