

Product availability : Stock - Normally stocked in distribution facility

Price\* : 117.00 USD



### Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit

### Complementary

Enclosure mounting	Surface
Number of 18 mm modules per row	3
Total number of 18 mm modules	3
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Provided equipment	1 marking kit
Type of front cover	Transparent
[In] rated current	32 A
Type of rail	DIN
Number of pre-cutouts PG ISO	1
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	3.15 in (80 mm)
Height	5.91 in (150 mm)
Depth	3.86 in (98 mm)
Colour	Door : transparent green Enclosure : light grey ( RAL 7035 )

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Standards	EN 50262 EN 50102 IEC 670 IEC 60439-3 IEC 60529
Fire resistance	1382 °F (750 °C) conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	UV resistant class 3 conforming to ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Ambient air temperature for operation	-13...140 °F (-25...60 °C)

## Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901855873
Nbr. of units in pkg.	20
Package weight(Lbs)	0.5999999999999998
Returnability	N
Country of origin	IT

## Contractual warranty

Warranty period	18 months
-----------------	-----------