

# Product data sheet

## Characteristics

# 150SV43A

## XFMR DRY 1PH .15KVA 120X240V-12/24V

Product availability : Stock - Normally stocked in distribution facility



Price\* : 276.00 USD



### Main

Product or component type	Buck and Boost Transformer
Box number	3A
NEMA degree of protection	NEMA 3R
Insulation temperature	221 °F (105 °C)
Primary voltage	120 x 240 V
Rated power in VA	0.15 kVA
Secondary voltage	12/24 V
Temperature rise	55 °C

### Ordering and shipping details

Category	16265 - BUCK & BOOST
Discount Schedule	PE2
GTIN	00785901876090
Nbr. of units in pkg.	1
Package weight(Lbs)	7.799999999999998
Returnability	Y
Country of origin	MX

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1430 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---