Product data sheet Characteristics

2510FG5

FHP Manual Starter - NEMA 1 - 1P - Key Operated w/Guard - No Indicator - 277VAC

Product availability: Stock - Normally stocked in distribution facility



Price*: 100.00 USD





Main

TTT GITT		<u>c</u>
Product or component type	Single Unit Manual Starter	
Range of product	F	99
Thermal overload type	Melting alloy	#

Complementary

16 A	
0.5" and 0.75" knock-outs (top and bottom)	
1 hp at 115 V AC	
1 hp at 230 V AC	
1 hp at 277 V AC	
277 V AC	
1P	
Toggle switch (with lock-off)	
1 phase	
No indicator	
Manual	
Non reversing	
Screw clamp terminals	
AWG 14AWG 12 (copper)	
4.25 in	
2.44 in	
2.88 in	
	0.5" and 0.75" knock-outs (top and bottom) 1 hp at 115 V AC 1 hp at 230 V AC 1 hp at 277 V AC 277 V AC 1P Toggle switch (with lock-off) 1 phase No indicator Manual Non reversing Screw clamp terminals AWG 14AWG 12 (copper) 4.25 in 2.44 in

Environment

Product certifications	CE	È
. To duot continuations	UL listed file E42243 CCN NLRV	<u>a</u> .
	CSA LR25490 class 3211 05	<u>a</u>

NEMA degree of protection	NEMA 1 plastic standard size
Ordering and shipping detail	s
Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901554011
Nbr. of units in pkg.	3
Package weight(Lbs)	0.810000000000005
Returnability	Υ
Country of origin	MX
Offer Sustainability	
Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant
	Will not be compliant

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will not be compliant	
	Will not be compliant	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months