

2510MCO3

Manual Starter - Open Device - Buttons - 3P - Size M1 - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price* : 366.80 USD



Main

Product or component type	Manual Starter
Range of product	M
Product certifications	CSA UL listed
Auxiliary contact composition	Without
NEMA degree of protection	Not rated (open device)
Local signalling	No indicator
Motor power hp	7.5 hp 200...230 V AC 3 phases 10 hp 380...575 V AC 3 phases
System Voltage	600 V AC
NEMA size	M-1
Poles description	3P
Control type	Push-button
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901792208
Nbr. of units in pkg.	1
Package weight(Lbs)	2.2000000000000002
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------