

Product data sheet

Characteristics

2510TBG2

Manual Starter - NEMA 1 - Toggle - 3P - Size M0 - No Indicator - 600VAC

Product availability : Stock - Normally stocked in distribution facility



Price* : 317.10 USD



Main

Product or component type	Manual Starter
Range of product	T
NEMA size	M-0

Complementary

Control type	Toggle switch
Local signalling	No indicator
Motor power hp	3 hp at 200...230 V AC 3 phases 5 hp at 380...575 V AC 3 phases
System Voltage	600 V AC
Poles description	3P
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	3
AWG gauge	AWG 14...AWG 8 (copper)
Auxiliary contact composition	Without
Height	8.63 in
Width	5 in
Depth	4.13 in

Environment

Product certifications	UL listed file E42243 CCN NLRV CSA LR60905 class 3211 05
NEMA degree of protection	NEMA 1 painted sheet steel

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901795612
Nbr. of units in pkg.	1
Package weight(Lbs)	4.2400000000000002
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------