Product data sheet Characteristics

750SV46FTRFMR DRY 1PH .75KVA 120X240V-16/32V

Product availability: Stock - Normally stocked in distribution facility





Price*: 552.00 USD



Main

Main		
Product or component type	Buck and Boost Transformer	
Box number	6A	
NEMA degree of protection	NEMA 3R	
Insulation temperature	356 °F (180 °C)	
Primary voltage	120 x 240 V	
Rated power in VA	0.75 kVA	
Secondary voltage	16/32 V	
Temperature rise	115 °C	

Ordering and shipping details

Category	16265 - BUCK & BOOST	,
Discount Schedule	PE2	
GTIN	00785901019947	
Nbr. of units in pkg.	1	
Package weight(Lbs)	17.35000000000001	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

RoHS (date code: YYWW) Compliant - since 1430 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity REACh Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold	.9
REACh Reference not containing SVHC above the threshold	. <u>.</u> 2
	. .
Reference not containing SVHC above the threshold	
Product environmental profile Available	
Product end of life instructions Need no specific recycling operations	

Warranty period

18 months