

Product data sheet

Characteristics

8501KP13P14V14

RELAY 240VAC 6.6AMP TYPE K +OPTIONS

Product availability : Stock - Normally stocked in distribution facility



Price* : 53.00 USD



Main

Range of product	8501K
Product or component type	Relay
Contacts material	Silver tin oxide
Switch function	3PDT
[Uc] control circuit voltage	24 V AC
Rated power in hp	0.33 hp 120 V 0.5 hp 240 V
Maximum switching voltage	240 V AC
Mounting support	Socket
Ambient air temperature for operation	-40...113 °F
Shape of pin	Tubular
Product certifications	UL recognized CSA RoHS CE
Operating time	12 ms pick-up 12 ms drop-out
Local signalling	Green indicator on
Control type	Without
Product compatibility	8501NR62 8501NR61
Relay type	General purpose

Ordering and shipping details

Category	21141 - 8501 KP
Discount Schedule	CP2
GTIN	00785901490647
Nbr. of units in pkg.	1
Package weight(Lbs)	0.2000000000000001

Returnability	Y
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------