

# Product data sheet

## Characteristics

# 8501XB40

## NEMA Control Relay Adder Deck with 4 NO Contacts

Product availability : Stock - Normally stocked in distribution facility



Price\* : 98.00 USD



### Main

Range of product	8501X
Relay type	Control relay
Product or component type	Adder deck

### Complementary

Rated breaking capacity	6 kA at: 120 V AC for: inductive load control circuit per UL 508 3 kA at: 240 V AC for: inductive load control circuit per UL 508 1.5 kA at: 480 V AC for: inductive load control circuit per UL 508 1.2 kA at: 600 V AC for: inductive load control circuit per UL 508 10 kA at: <= 600 V AC for: resistive load control circuit per UL 508 1.1 kA at: 125 V DC for: inductive load control circuit per UL 508 0.55 kA at: 250 V DC for: inductive load control circuit per UL 508 0.2 kA at: 301...600 V DC for: inductive load control circuit per UL 508 4 kA at: 125 V DC for: resistive load control circuit per UL 508 0.8 kA at: 250 V DC for: resistive load control circuit per UL 508
[Icm] rated short-circuit making capacity	60 kA at: 120 V AC for: inductive load control circuit per UL 508 30 kA at: 240 V AC for: inductive load control circuit per UL 508 15 kA at: 480 V AC for: inductive load control circuit per UL 508 12 kA at: 600 V AC for: inductive load control circuit per UL 508 10 kA at: <= 600 V AC for: resistive load control circuit per UL 508 1.1 kA at: 125 V DC for: inductive load control circuit per UL 508 0.55 kA at: 250 V DC for: inductive load control circuit per UL 508 0.2 kA at: 301...600 V DC for: inductive load control circuit per UL 508 4 kA at: 125 V DC for: inductive load control circuit per UL 508 0.8 kA at: 250 V DC for: resistive load control circuit per UL 508
Contacts type and composition	4 NO 4 standard contact cartridges
Electrical connection	Screw clamp terminals
AWG gauge	AWG 18...AWG 12 copper
Tightening torque	1.02...1.36 N.m control circuit screw terminals

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

Product certifications	CE UL recognized E78403 CCN NKCR2 CSA LR60905 class 3211 02
------------------------	---

## Ordering and shipping details

Category	21159 - 8501 X ACCESSORIES
Discount Schedule	CP2
GTIN	00785901537328
Nbr. of units in pkg.	1
Package weight(Lbs)	0.55000000000000004
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1332 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------