

Product availability : Stock - Normally stocked in distribution facility



Price* : 1929.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	90 A
Product certifications	CSA NEMA UL listed
Control circuit	Separate control circuit
Control type	No control units
NEMA degree of protection	NEMA 1 painted sheet steel
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	3
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901788317
Nbr. of units in pkg.	1
Package weight(Lbs)	35.78000000000001

Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------