

Product availability : Stock - Normally stocked in distribution facility



Price\* : 315.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	50 VA
Primary voltage	220/380/440/550 V 208/360/416/520 V 230/400/460/575 V 240/416/480/600 V
Secondary voltage	85/104/115 V 95/115/125 V 90/110/120 V 99/120/130 V
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	50 VA
Primary voltage	208/360/416/520 V : 85/104/115 V 220/380/440/550 V : 90/110/120 V 230/400/460/575 V : 95/115/125 V 240/416/480/600 V : 99/120/130 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	2.89 in
Width	3.38 in
Depth	4.43 in
Material	Copper winding
Product compatibility	FSC23

### Environment

Product certifications	CE CSA file LR37055 guide 184-N-90
------------------------	---------------------------------------

UL listed file E61239

NEMA degree of protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

### Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901327240
Nbr. of units in pkg.	1
Package weight(Lbs)	4.2199999999999998
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

### Contractual warranty

Warranty period	10 years
-----------------	----------