

GV3ME80

TeSys GV3 - Circuit breaker - thermal-magnetic - 56...80 A - screw clamp terminals

Product availability : Stock - Normally stocked in distribution facility

Price* : 660.00 USD



Main

Range	TeSys
Product name	TeSys GV3
Device short name	GV3ME
Product or component type	Circuit breaker
Device application	Motor
Trip unit technology	Thermal-magnetic

Complementary

Poles description	3P
Network type	AC
Utilisation category	AC-3 conforming to IEC 60947-4-1 Category A conforming to IEC 60947-2
Network frequency	50/60 Hz conforming to IEC 60947-4-1
Mounting mode	By clips By screws
Mounting support	Plate Rail
Mounting position	Horizontal Vertical
Motor power kW	45 kW at 500 V AC 50/60 Hz 55 kW at 690 V AC 50/60 Hz 37 kW at 400/415 V AC 50/60 Hz
Breaking capacity	15 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 4 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 2 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 % at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2

100 % at 690 V AC 50/60 Hz conforming to IEC 60947-2
 50 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2
 60 % at 440 V AC 50/60 Hz conforming to IEC 60947-2

Control type	Push-button
[In] rated current	56...80 A
Trip unit rating	56...80 A
Magnetic tripping current	1040 A
System Voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ith] conventional free air thermal current	80 A conforming to IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Power dissipation per pole	8 W
Mechanical durability	30000 cycles
Electrical durability	30000 cycles AC-3 at 440 V
Operating rate	25 cyc/h
Rated duty	Continuous conforming to IEC 60947-4-1
Connections - terminals	Screw clamp terminals 1 cable(s) 0...0.05 in ² (2.5...35 mm ²) - cable stiffness : solid Screw clamp terminals 1 cable(s) 0...0.02 in ² (2.5...16 mm ²) - cable stiffness : flexible - without cable end Screw clamp terminals 1 cable(s) 0...0.02 in ² (2.5...16 mm ²) - cable stiffness : flexible - with cable end
Tightening torque	44.25 lbf.in (5 N.m) - on screw clamp terminals
Phase failure sensitivity	Yes conforming to IEC 60947-4-1
Height	4.72 in (120 mm)
Width	2.41 in (61.2 mm)
Depth	4.45 in (113 mm)
Product weight	1.54 lb(US) (0.7 kg)

Environment

Standards	NF EN DIN EN 60947-2 DIN EN 60947-4-1 EN/IEC BS EN
Product certifications	UL LROS (Lloyds register of shipping) CSA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
IK degree of protection	IK04
Ambient air temperature for operation	-4...140 °F (-20...60 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Fire resistance	1760 °F (960 °C) conforming to IEC 60695-2-1
Operating altitude	9842.52 ft (3000 m)

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901212379
Nbr. of units in pkg.	1
Package weight(Lbs)	1.5900000000000001
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------
