

Product availability : Stock - Normally stocked in distribution facility



Price* : 2886.00 USD



Main

Disconnecter device type	Non-fusible disconnect switch
Enclosure type	Enclosure hazardous location indoor Enclosure exposure to damp heat in service
Series name	Heavy duty

Complementary

[In] rated current	60 A
AWG gauge	AWG 14...AWG 6 copper
Device mounting	Surface
Electrical connection	Screw clamp terminal
Enclosure material	Cast aluminium
Interlocking type	Without electrical interlock
Number of poles	3
Permissible voltage	<= 600 V AC <= 250 V DC
Short-circuit protection	10 kA
Switch function	TPST
Wiring configuration	Without neutral

Environment

NEMA degree of protection	NEMA 7/9
Product certifications	CSA UL listed

Ordering and shipping details

Category	00066 - MISC H/D SWITCHES
Discount Schedule	DE1

GTIN	00785901083870
Nbr. of units in pkg.	1
Package weight(Lbs)	28.07
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0313 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------