Product data sheet Characteristics

LA36200 3P 200A 600V LA MOULDED CASE CIRCUIT BREAKER

Product availability: Stock - Normally stocked in distribution facility





Price*: 4944.00 USD



Main

		<u> </u>
Product or component type	Circuit breaker	7
Range of product	I-Line	
Trip unit technology	Thermal-magnetic	***************************************
Breaking capacity code	A	#.

Complementary

		<u> </u>
Line Rated Current	200 A	
Poles description	3P	
Breaking capacity	25 kA at 600 V AC 42 kA at 240 V AC 30 kA at 480 V AC	, d
System Voltage	250 V DC 600 V AC	
Mounting mode	I-Line	<u>.</u>
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 1600 kcmil (aluminium/copper) 1 cable(s) AWG 1250 kcmil (aluminium/copper) 2 cable(s)	11.00
Terminal identifier	AL400LA	
Magnetic hold current	1000 A	
Magnetic tripping current	2000 A	
Wiring configuration	3-wire	<u>.</u> 9. 5

Environment

	Product certifications	CSA UL listed

Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901339298
Nbr. of units in pkg.	1
Package weight(Lbs)	18.08000000000002
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

•	
Warranty period	18 months