## Product data sheet Characteristics

# LUA1C20

## signalling contacts LUA - 2 NO

Product availability: Stock - Normally stocked in distribution facility

Price\*: 34.50 USD



#### Main

Range	TeSys
Device short name	LUA1
Product or component type	Auxiliary contact

#### Complementary

4.0			
Main			
Range	TeSys		
Device short name	LUA1		
Product or component type	Auxiliary contact		
	·		
Complementary			
Auxiliary contact composition	2 NO		
Signalling function	Fault signalling		
Cignaling function	Indicating rotary knob in ready position		
System Voltage	<= 250 V AC		
	<= 250 V DC		
[Ui] rated insulation voltage	250 V conforming to CSA 250 V conforming to IEC 60947-5-1		
	250 V conforming to UL		
[lth] conventional free air thermal current	2.5 A		
Minimum switching voltage	17 V		
Minimum switching current	5 mA		
Product weight	0.07 lb(US) (0.03 kg)		
Connections - terminals	Screw clamp terminals		
Ordering and shipping details			
Category	22399 - TESYS U, ACCESSORIES		
Discount Schedule	l11		
GTIN	00785901222170		
Nbr. of units in pkg.	1		
Package weight(Lbs)	7.000000000000007E-2		
Returnability	Υ		
Country of origin	CZ		

### Ordering and shipping details

Category	22399 - TESYS U, ACCESSORIES	
Discount Schedule	l11	
GTIN	00785901222170	
Nbr. of units in pkg.	1	
Package weight(Lbs)	7.000000000000007E-2	
Returnability	Υ	
Country of origin	CZ	

Warranty period

18 months